

| View C | nline at https://aerobasegroup.com/nsn/5306-01-038-3793 |
|---------|---|
| Thread | l Class: |
| 2a | |
| Thread | Direction: |
| Right-h | and |
| Thread | Length: |
| 1.500 i | nches |
| Eye In | side Diameter: |
| 0.760 i | nches |
| Shank | Length: |
| 3.560 i | nches |
| Eye St | ock Diameter: |
|).250 i | nches |
| Overa | I Length: |
| 10.190 | inches |
| Thread | Diameter: |
|).250 i | nches |
| Thread | ly Qty Per Inch (tpi): |
| 28 | |
| Distan | ce From Center Of Eye To Shank End: |
| 9.560 i | nches |
| Distan | ce From Threaded End To Shank Hole Center: |
| 3.060 i | nches first hole |
| Materi | al: |
| Steel c | omp 1018 |
| Surfac | e Treatment: |
| Cadmi | um |
| Surfac | e Treatment Specification: |
| ຊ-p-4 | 16, type 2, class 2 federal specification single treatment response |
| Style [| Designator: |
| Round | , open |
| Thread | I Series Designator: |
| Unf | |
| Shelf I | .ife: |
| N/a | |
| Unit O | f Measure: |
| | |
| Demili | tarization: |
| No | |
| Fiig: | |
| A003b | 0 |