

View Online at <https://aerobasegroup.com/nsn/5306-01-038-4745>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.352 inches and 0.448 inches

**Fastener Length:**

Between 1.391 inches and 1.431 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**Shoulder Diameter:**

0.309 inches first shoulder and 0.312 inches first shoulder

**Shoulder Length:**

0.948 inches first shoulder and 0.968 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.203 inches first hole and 1.263 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Surface Treatment:**

Chromate and cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1297 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0