

View Online at <https://aerobasegroup.com/nsn/5306-01-038-6365>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.495 inches and 0.625 inches

Fastener Length:

Between 0.595 inches and 0.625 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.204 inches and 0.222 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

Extended Washer Diameter:

Between 0.513 inches and 0.531 inches

Extended Washer Thickness:

Between 0.048 inches and 0.066 inches

Locking Feature:

Locking teeth bearing surface of head

Thread Diameter:

0.250 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

115000 pounds per square inch

Hardness Rating:

22.0 rockwell c and 35.0 rockwell c

Material:

Steel comp 1018 or steel comp 1021 or steel comp 1022

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Zinc

Surface Treatment Specification:

Gm 4342-m fscm 89955 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0