

View Online at <https://aerobasegroup.com/nsn/5306-01-040-3361>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.568 inches and 0.618 inches

Fastener Length:

Between 0.953 inches and 0.983 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.309 inches and 0.329 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

200000 pounds per square inch

Hole Configuration Style:

Square longitudinal hole

Material:

Iron alloy 660

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Specification Data:

81205-bacs12le professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0