

View Online at <https://aerobasegroup.com/nsn/5306-01-040-3361>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.568 inches and 0.618 inches

**Fastener Length:**

Between 0.953 inches and 0.983 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.309 inches and 0.329 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.060 inches

**Hole Diameter:**

0.055 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

200000 pounds per square inch

**Hole Configuration Style:**

Square longitudinal hole

**Material:**

Iron alloy 660

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Specification Data:**

81205-bacs12le professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0