

View Online at <https://aerobasegroup.com/nsn/5306-01-040-3365>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.445 inches and 0.495 inches

**Fastener Length:**

Between 1.643 inches and 1.673 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.472 inches all holes and 1.522 inches all holes

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Specification Data:**

81205-bacb30lj manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0