

View Online at <https://aerobasegroup.com/nsn/5306-01-040-4696>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.641 inches and 0.691 inches

**Fastener Length:**

Between 3.901 inches and 3.931 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.375 inches and 0.390 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 3.240 inches and 3.260 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6212 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.