## NSN 5306-01-040-5482

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-040-5482

## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

1.003 inches

## Fastener Length:

3.810 inches

#### Head Style:

Hexagon

#### Head Height:

0.500 inches

#### Width Between Flats:

1.750 inches

#### Shoulder Diameter:

1.246 inches first shoulder and 1.248 inches first shoulder

#### Shoulder Length:

2.467 inches first shoulder

## Shank Unthreaded Hole Diameter:

0.141 inches first hole

#### **Thread Diameter:**

1.000 inches

## Thready Qty Per Inch (tpi):

12

## Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

## Distance From Head Largest Bearing Surface To Shank Hole Center:

3.510 inches first hole

## Shoulder Shape:

Round first shoulder

## Material:

Steel

## Material Specification:

Astm a322 assn standard single material response or mil-s-46172 military specification single material response or astm a331 assn standard single material response

#### Surface Treatment:

Cadmium

## **Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response or qq-p-416, type 3, class 2 federal specification single treatment response

## **Thread Series Designator:**

Unf

## Shelf Life:

N/a

# NSN 5306-01-040-5482

Shoulder Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-46172 spec.

