

View Online at <https://aerobasegroup.com/nsn/5306-01-042-1753>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.427 inches and 0.466 inches

Fastener Length:

1.830 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.250 inches

Head Height:

0.120 inches

Width Between Flats:

Between 1.053 inches and 1.066 inches

Shoulder Diameter:

Between 0.7485 inches and 0.7490 inches

Shoulder Length:

Between 1.310 inches and 1.320 inches

Shank Unthreaded Hole Diameter:

0.111 inches first hole

Concentric Hole Depth:

1.190 inches

Concentric Hole Diameter:

0.375 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Criticality Code Justification:

Aavh

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.668 inches first hole

Material:

Steel

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lcp 1067, fscm 36659 mfr ref single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.