## NSN 5306-01-043-1871

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-043-1871

| Thread Class:                           |
|---|
| 3a                                      |
| Thread Direction:                       |
| Right-hand                              |
| Thread Length:                          |
| Between 0.455 inches and 0.505 inches   |
| Fastener Length:                        |
| Between 1.840 inches and 1.870 inches   |
| Head Style:                             |
| Double hexagon w/hole                   |
| Head Height:                            |
| Between 0.338 inches and 0.358 inches   |
| Width Between Flats:                    |
| Between 0.367 inches and 0.376 inches   |
| Extended Washer Diameter:               |
| Between 0.521 inches and 0.531 inches   |
| Extended Washer Thickness:              |
| Between 0.072 inches and 0.092 inches   |
| Hole Diameter:                          |
| 0.055 inches                            |
| Grip Diameter:                          |
| Between 0.3110 inches and 0.3120 inches |
| Thread Diameter:                        |
| 0.312 inches                            |
| Grip Length:                            |
| Between 1.365 inches and 1.385 inches   |
| Hole Quantity:                          |
| 4                                       |
| Hole Type:                              |
| Drilled                                 |
| Thready Qty Per Inch (tpi):             |
| 24                                      |
| Min. Tensile Strength (psi):            |
| 220000 pounds per square inch           |
| Hardness Rating:                        |
| 46.0 rockwell c and 48.0 rockwell c     |
| Hole Configuration Style:               |
| Hexagon longitudinal hole               |
| Product Name:                           |
| Navy special project                    |
| Material:                               |
| Steel comp h11                          |

Steel comp h11

## NSN 5306-01-043-1871

Shear Bolt - Page 2 of 2

A003b0



| Surface Treatment:  |
|---|
| Cadmium   |
| Thread Series Designator:                                 |
| Unjf  |
| Specification Data:                                       |
| 26512-gb511w professional/industrial association standard |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |