

View Online at <https://aerobasegroup.com/nsn/5306-01-043-4297>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.507 inches

Fastener Length:

Between 2.075 inches and 2.122 inches

Head Style:

Double hexagon

Head Height:

Between 0.247 inches and 0.267 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Shank Unthreaded Hole Diameter:

0.101 inches all holes and 0.111 inches all holes

Thread Diameter:

0.438 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.950 inches all holes and 1.982 inches all holes

Material:

Steel comp h11

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

26512-gb511b manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0