

View Online at <https://aerobasegroup.com/nsn/5306-01-043-5722>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.325 inches and 0.392 inches

**Fastener Length:**

Between 1.710 inches and 1.757 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.177 inches and 0.197 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3108 inches and 0.3117 inches

**Shank Unthreaded Hole Diameter:**

0.071 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.591 inches first hole and 1.623 inches first hole

**Material:**

Steel comp h11

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjf

**Specification Data:**

85495-b-17020 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0