

View Online at <https://aerobasegroup.com/nsn/5306-01-043-5722>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.325 inches and 0.392 inches

Fastener Length:

Between 1.710 inches and 1.757 inches

Head Style:

Double hexagon

Head Height:

Between 0.177 inches and 0.197 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.071 inches first hole and 0.081 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.591 inches first hole and 1.623 inches first hole

Material:

Steel comp h11

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

85495-b-17020 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0