## NSN 5306-01-043-5725

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-043-5725
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.607 inches and 0.674 inches
Fastener Length:
Between 1.929 inches and 1.976 inches
Head Style:
Double hexagon
Head Height:
Between 0.340 inches and 0.360 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Shank Unthreaded Hole Diameter:
0.136 inches first hole and 0.146 inches first hole
Thread Diameter:
0.625 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.825 inches first hole
Product Name:
Navy special project
Material:
Steel comp h11
Surface Treatment:
Cadmium
Thread Series Designator:
Unjf
Specification Data:
26512-gb511b professional/industrial association standard
Shelf Life:
N/a

## NSN 5306-01-043-5725

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0