## NSN 5306-01-043-5725

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-043-5725



### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.607 inches and 0.674 inches

#### Fastener Length:

Between 1.929 inches and 1.976 inches

#### **Head Style:**

Double hexagon

#### Head Height:

Between 0.340 inches and 0.360 inches

#### Width Between Flats:

Between 0.928 inches and 0.940 inches

#### Grip Diameter:

Between 0.6230 inches and 0.6240 inches

#### Shank Unthreaded Hole Diameter:

0.136 inches first hole and 0.146 inches first hole

#### **Thread Diameter:**

0.625 inches

#### Grip Length:

Between 1.302 inches and 1.322 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

#### Distance From Head Largest Bearing Surface To Shank Hole Center:

1.825 inches first hole

#### **Product Name:**

Navy special project

#### Material:

Steel comp h11

#### Surface Treatment:

Cadmium

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

26512-gb511b professional/industrial association standard

#### Shelf Life:

N/a

# NSN 5306-01-043-5725

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

