

View Online at <https://aerobasegroup.com/nsn/5306-01-043-5732>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.815 inches and 0.865 inches

**Fastener Length:**

Between 3.700 inches and 3.730 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.281 inches and 0.296 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Grip Diameter:**

Between 0.5610 inches and 0.5615 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 2.865 inches and 2.885 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.472 inches first hole and 3.522 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Titanium alloy uns r54520

**Material Specification:**

Nas621 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1266 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0