

View Online at <https://aerobasegroup.com/nsn/5306-01-043-8045>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 2.188 inches and 2.281 inches

**Fastener Length:**

Between 2.250 inches and 2.312 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.131 inches and 0.151 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Hole Diameter:**

0.046 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.031 inches and 0.062 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Special Features:**

Shank end slotted 0.061 in. Min 0.077 in. Maximum wide by 0.097 in. Min, 0.130 in. Maximum lg

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas428 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0