

View Online at <https://aerobasegroup.com/nsn/5306-01-044-0737>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.507 inches

Fastener Length:

Between 1.575 inches and 1.622 inches

Head Style:

Double hexagon

Head Height:

Between 0.247 inches and 0.267 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Shank Unthreaded Hole Diameter:

0.101 inches first hole and 0.111 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.450 inches first hole and 1.482 inches first hole

Product Name:

Navy special project

Material:

Steel comp h11

Surface Treatment:

Cadmium or cadmium and chromate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0