

View Online at <https://aerobasegroup.com/nsn/5306-01-044-7467>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.966 inches and 1.033 inches

Fastener Length:

Between 4.101 inches and 4.148 inches

Head Style:

Double hexagon

Head Height:

Between 0.458 inches and 0.478 inches

Width Between Flats:

Between 1.239 inches and 1.252 inches

Grip Diameter:

Between 0.8730 inches and 0.8740 inches

Shank Unthreaded Hole Diameter:

0.136 inches first hole and 0.146 inches first hole

Thread Diameter:

0.875 inches

Grip Length:

Between 3.115 inches and 3.135 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.967 inches first hole and 3.999 inches first hole

Product Name:

Navy special project

Material:

Steel comp h11

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Specification Data:

85495-b-17020 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0