NSN 5306-01-044-7467



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-044-7467 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.966 inches and 1.033 inches **Fastener Length:** Between 4.101 inches and 4.148 inches **Head Style:** Double hexagon **Head Height:** Between 0.458 inches and 0.478 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Grip Diameter:** Between 0.8730 inches and 0.8740 inches **Shank Unthreaded Hole Diameter:** 0.136 inches first hole and 0.146 inches first hole **Thread Diameter:** 0.875 inches **Grip Length:** Between 3.115 inches and 3.135 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 3.967 inches first hole and 3.999 inches first hole **Product Name:** Navy special project Material: Steel comp h11 **Surface Treatment: Passivate Thread Series Designator:**

Unjf

Specification Data:

85495-b-17020 manufacturers standard

Shelf Life:

N/a

NSN 5306-01-044-7467

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0