NSN 5306-01-044-7470

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-044-7470 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.948 inches and 0.978 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Chromate **Surface Treatment Specification:** Qq-p-416 ty1 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1303 professional/industrial association standard Shelf Life:

Unit Of Measure:

N/a

NSN 5306-01-044-7470

Shear Bolt - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0