

View Online at <https://aerobasegroup.com/nsn/5306-01-044-9538>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.342 inches

Fastener Length:

1.860 inches

Head Style:

Hexagon

Head Height:

0.120 inches

Width Between Flats:

Between 0.744 inches and 0.750 inches

Shoulder Diameter:

0.4985 inches first shoulder and 0.4993 inches first shoulder

Shoulder Length:

1.450 inches first shoulder

Shank Unthreaded Hole Diameter:

0.075 inches first hole and 0.080 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.750 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lcp 1067, class 3, type 2, fscm 36659 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.