

View Online at <https://aerobasegroup.com/nsn/5306-01-044-9538>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.342 inches

**Fastener Length:**

1.860 inches

**Head Style:**

Hexagon

**Head Height:**

0.120 inches

**Width Between Flats:**

Between 0.744 inches and 0.750 inches

**Shoulder Diameter:**

0.4985 inches first shoulder and 0.4993 inches first shoulder

**Shoulder Length:**

1.450 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.075 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.750 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626, cond c4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Lcp 1067, class 3, type 2, fscm 36659 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.