

View Online at <https://aerobasegroup.com/nsn/5306-01-044-9540>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.330 inches and 0.370 inches

Fastener Length:

Between 3.460 inches and 3.500 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.125 inches

Head Height:

0.125 inches

Width Between Flats:

0.875 inches

Shoulder Diameter:

Between 0.6237 inches and 0.6242 inches

Shoulder Length:

3.130 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Concentric Hole Depth:

2.680 inches

Concentric Hole Diameter:

Between 0.623 inches and 0.624 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Criticality Code Justification:

Aavh

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.360 inches first hole

Material:

Steel

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lcp 1067, fscm 16659 mfr ref single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.