## NSN 5306-01-045-2454

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-045-2454 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.271 inches and 0.323 inches **Fastener Length:** Between 0.812 inches and 0.844 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.200 inches and 0.206 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.521 inches and 0.541 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

## NSN 5306-01-045-2454

Internal Wrenching Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0