

View Online at <https://aerobasegroup.com/nsn/5306-01-046-0562>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.760 inches and 1.800 inches

Fastener Length:

Between 6.270 inches and 6.290 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 1.145 inches and 1.165 inches

Width Between Flats:

Between 1.302 inches and 1.322 inches

Extended Washer Diameter:

Between 2.115 inches and 2.125 inches

Extended Washer Thickness:

Between 0.259 inches and 0.279 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 1.2475 inches and 1.2490 inches

End Application:

Spec item

Thread Diameter:

1.250 inches

Grip Length:

Between 4.490 inches and 4.510 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Hexagon flats

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0