

View Online at <https://aerobasegroup.com/nsn/5306-01-046-3261>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.282 inches and 0.333 inches

**Fastener Length:**

Between 1.918 inches and 1.938 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2483 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.500 inches and 1.516 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.818 inches first hole and 1.848 inches first hole

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Retaining ring on shank

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0