NSN 5306-01-046-5292

Machine Bolt - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5306-01-046-5292



Thread Direction: Right-hand Thread Length: Between 0.740 inches and 0.820 inches Fastener Length: Between 1.552 inches and 1.572 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.752 inches and 0.812 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 195000 pounds per square inch Hardness Rating: 42.0 rockwell c and 46.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Steel comp 601

NSN 5306-01-046-5292

Machine Bolt - Page 2 of 2



Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0