

View Online at <https://aerobasegroup.com/nsn/5306-01-047-0359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.450 inches

**Fastener Length:**

Between 1.160 inches and 1.190 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Product Name:**

Navy special project

**Special Features:**

Patch type element on threads

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1224 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0