## NSN 5306-01-047-7834

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-047-7834

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 0.785 inches and 0.815 inches
Head Style:
Hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.076 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Surface Finish:
63.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate

## NSN 5306-01-047-7834

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0