

View Online at <https://aerobasegroup.com/nsn/5306-01-049-0014>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.365 inches and 0.415 inches

Fastener Length:

Between 0.500 inches and 0.530 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.204 inches and 0.224 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.359 inches and 0.369 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

Hole Diameter:

0.037 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.115 inches and 0.135 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0