## NSN 5306-01-049-0635

Shear Bolt - Page 1 of 2

---

View Online at https://aerobasegroup.com/nsn/5306-01-049-0635



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.568 inches and 0.618 inches Fastener Length: Between 1.453 inches and 1.483 inches **Head Style:** Hexagon **Head Height:** Between 0.309 inches and 0.329 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.040 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches **End Application:** W/s: aircraft, c-18a, ec-18b; joint stars target radar system; aircraft, awacs, e-3a **Thread Diameter:** 0.312 inches Grip Length: Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 200000 pounds per square inch Material: Iron alloy 660 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

## NSN 5306-01-049-0635

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

