

View Online at <https://aerobasegroup.com/nsn/5306-01-049-3003>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.364 inches and 0.414 inches

**Fastener Length:**

Between 2.686 inches and 2.716 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.302 inches and 2.322 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.560 inches first hole and 2.610 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

81205-bacb30nf manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0