NSN 5306-01-049-3145

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-049-3145

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.335 inches and 0.375 inches |
| Fastener Length: |
| Between 1.210 inches and 1.250 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.457 inches and 0.469 inches |
| Head Height: |
| Between 0.305 inches and 0.313 inches |
| First Diameter From Head: |
| 0.220 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.875 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| Between 0.250 inches and 0.253 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Material: |
| Steel comp 303 or steel comp 305 or steel comp 316 |
| Material Specification: |
| Aisi assn standard all material responses |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 type 2 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5306-01-049-3145

Internal Wrenching Bolt - Page 2 of 2

Fiig: A003b0

