## NSN 5306-01-049-4699



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-049-4699 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.329 inches and 1.359 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Hole Diameter:** 0.070 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.865 inches and 0.885 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Hexagon longitudinal hole Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-049-4699

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0