

View Online at <https://aerobasegroup.com/nsn/5306-01-050-2616>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.594 inches

**Fastener Length:**

Between 2.272 inches and 2.292 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.328 inches

**Grip Diameter:**

Between 0.5607 inches and 0.5616 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Single Shear Strength:**

132000 pounds per square inch

**Head Minor Diameter:**

1.049 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.006 inches first hole and 2.026 inches first hole

**Material:**

Stainless steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0