NSN 5306-01-050-4976

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-050-4976 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.602 inches and 0.662 inches **Fastener Length:** Between 3.992 inches and 4.022 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.492 inches and 0.501 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 3.360 inches and 3.390 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1005 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-01-050-4976

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.