

View Online at <https://aerobasegroup.com/nsn/5306-01-052-0023>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.498 inches

**Fastener Length:**

1.898 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

0.750 inches

**Shoulder Diameter:**

0.498 inches first shoulder and 0.499 inches first shoulder

**Shoulder Length:**

1.230 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.108 inches first hole and 0.113 inches first hole

**Thread Diameter:**

0.375 inches

**Thread Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.712 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Mil-s-5626, cond c4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Lc+77-1061, fscm 36659 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.