

View Online at <https://aerobasegroup.com/nsn/5306-01-053-2868>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.320 inches

**Fastener Length:**

1.695 inches

**Head Style:**

Hexagon

**Head Height:**

0.168 inches

**Width Between Flats:**

0.497 inches

**Shoulder Diameter:**

0.374 inches first shoulder

**Shoulder Length:**

1.320 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.535 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0