NSN 5306-01-053-6974

Close Tolerance Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-053-6974

view Online at https://aerobasegroup.com/nsn/5306-01-053-6974
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.364 inches and 0.414 inches
Fastener Length:
Between 0.936 inches and 0.966 inches
Head Style:
Undercut hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
28
28
28 Surface Finish:
28 Surface Finish: 32.0 microinches threads
28 Surface Finish: 32.0 microinches threads Material:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure:
28 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qaq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No