## NSN 5306-01-054-1546

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-054-1546 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.364 inches and 0.414 inches **Fastener Length:** Between 1.249 inches and 1.279 inches **Head Style:** Undercut hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Hole Diameter:** 0.051 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.865 inches and 0.885 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Hole Configuration Style:** Hexagon corners **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:** Unjf

## NSN 5306-01-054-1546

Close Tolerance Bolt - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0