

View Online at <https://aerobasegroup.com/nsn/5306-01-054-2506>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.395 inches

**Fastener Length:**

Between 0.917 inches and 0.947 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.737 inches first hole and 0.787 inches first hole

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6204 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.