
## NSN 5306-01-054-4597

Shear Bolt - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.320 inches and 0.370 inches Fastener Length: Between 1.642 inches and 1.672 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: 0.051 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches Grip Length: Between 1.302 inches and 1.322 inches **Hole Quantity:** 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5306-01-054-4597

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

