

View Online at <https://aerobasegroup.com/nsn/5306-01-055-3779>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.553 inches and 0.603 inches

Fastener Length:

Between 1.313 inches and 1.343 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 0.740 inches and 0.760 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.106 inches first hole and 1.156 inches first hole

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0