

View Online at <https://aerobasegroup.com/nsn/5306-01-055-4588>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.438 inches and 0.516 inches

Eye Inside Diameter:

Between 0.313 inches and 0.316 inches

Shoulder Thickness:

Between 0.078 inches and 0.109 inches

Shank Length:

Between 0.953 inches and 1.000 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

Between 0.672 inches and 0.703 inches

Overall Length:

Between 1.935 inches and 1.985 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Center Of Eye To Shank End:

Between 1.693 inches and 1.731 inches

Eye Outside Width:

Between 0.672 inches and 0.703 inches

Material:

Stainless steel

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.