

View Online at <https://aerobasegroup.com/nsn/5306-01-055-5142>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.380 inches

**Fastener Length:**

4.781 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

0.371 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Extended Washer Diameter:**

1.000 inches

**Extended Washer Thickness:**

Between 0.074 inches and 0.106 inches

**Shoulder Diameter:**

Between 0.748 inches and 0.749 inches

**Shoulder Length:**

Between 4.396 inches and 4.406 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Concentric Hole Depth:**

4.480 inches

**Concentric Hole Diameter:**

0.560 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.689 inches first hole and 4.699 inches first hole

**Material:**

Steel

**Material Specification:**

Mil-h-6875 military specification single material response

**Surface Treatment:**

Cadmium

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-h-6875 spec.