

View Online at <https://aerobasegroup.com/nsn/5306-01-055-5142>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.380 inches

Fastener Length:

4.781 inches

Head Style:

Hexagon extended washer

Head Height:

0.371 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Extended Washer Diameter:

1.000 inches

Extended Washer Thickness:

Between 0.074 inches and 0.106 inches

Shoulder Diameter:

Between 0.748 inches and 0.749 inches

Shoulder Length:

Between 4.396 inches and 4.406 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Concentric Hole Depth:

4.480 inches

Concentric Hole Diameter:

0.560 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.689 inches first hole and 4.699 inches first hole

Material:

Steel

Material Specification:

Mil-h-6875 military specification single material response

Surface Treatment:

Cadmium

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-h-6875 spec.