
Assembled Washer Bolt - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.164 inches and 0.280 inches

## Fastener Length:

Between 0.235 inches and 0.280 inches

### Head Style:

Button

Head Diameter:

Between 0.469 inches and 0.580 inches

### **Head Height:**

Between 0.141 inches and 0.171 inches

# Washer Quantity:

1

# Thread Diameter:

0.250 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

125000 pounds per square inch

# Primary Washer Style:

Flat

# **Special Features:**

Furnish with one o-ring manufactured to ams 3304 (-85 to 559 degrees f)

Material:

Steel comp 431 fastener

# Material Specification:

Ams3652 assn standard single material response primary washer

#### Surface Treatment:

Passivate fastener

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

# **Thread Series Designator:**

Unf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5306-01-056-7973

Assembled Washer Bolt - Page 2 of 2

Fiig: A003b0

