

View Online at <https://aerobasegroup.com/nsn/5306-01-057-3049>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.852 inches and 0.892 inches

**Fastener Length:**

Between 2.862 inches and 2.882 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.547 inches and 0.567 inches

**Width Between Flats:**

Between 0.615 inches and 0.635 inches

**Extended Washer Diameter:**

Between 0.928 inches and 0.938 inches

**Extended Washer Thickness:**

Between 0.123 inches and 0.133 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.990 inches and 2.010 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0