## NSN 5306-01-057-4275

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-057-4275

| Thread Class:  |
|--|
|  |
| 3a   |
| Thread Direction:  |
| Right-hand Thread Longton  |
| Thread Length:   |
| Between 0.298 inches and 0.348 inches  |
| Fastener Length:   |
| Between 0.558 inches and 0.588 inches  |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| Between 0.110 inches and 0.125 inches  |
| Width Between Flats:   |
| Between 0.367 inches and 0.376 inches  |
| Grip Diameter:   |
| Between 0.1885 inches and 0.1895 inches  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.240 inches and 0.260 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Surface Finish:  |
| 32.0 microinches threads   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416 ty2 cl2 federal specification single treatment response                                 |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas6303 professional/industrial association standard                                       |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5306-01-057-4275

Shear Bolt - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A003b0